



INB-52M2812M0A

SKU: 235341



Network Camera Bullet, 1920x1080, Day/Night, WDR, AI 2,8-12mm, IR, 12V, PoE, IP67

Main Features

- 1/2.8" Sony STARVIS CMOS sensor, 2 MP/60fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR Noise Reduction
- Motorized varifocal lens 2.8-12mm
- Smart Codec H.265/H.264, multi-streaming
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Supports ONVIF Profile S and Profile T
- Multilingual menu navigation (OSD)
- Local storage via Micro SD card
- Supports audio and external alarm input and output
- Power supply 12VDC or PoE IEEE 802.3af
- IR LED illumination, IP67

Specifications

Dimensions (HxWxD)	83,88x87,4x242mm
Series	eneo IN-Series
Camera Type	Face recognition, License plate recognition, People Count, Retail Intelligence
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080

INB-52M2812M0A

Continuation of the specifications

Image Transmission Rate	60 fps
Day&Night Switch	ICR
Sensitivity	0,002 Lux
Sensitivity 2	at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR, DOL-WDR 120dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	2,8 - 12 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
Horizontal Angle of View	101 - 33°
Vertical Angle of View	52 - 18°
Illumination	infrared
Housing	outdoor
Color (housing)	Pantone P 179-1, RAL9003
Housing material	aluminium
Heater	no
Blower	no
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	audio detection, Crowd detection, Face detection, face recognition, Heatmapping, intrusion, License plate detection, license plate recognition, Line detection, Object classification (person / vehicle), Object left,removed, Queue management, trip wire detection with counting and direction detection
Mounting_4	ceiling mount, wall mount
Supply voltage	12VDC, PoE
Power consumption	7W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-35°C ~ +55°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T

INB-52M2812M0A

Continuation of the specifications

Protection rating	IP67
Camera built	Bullet
Audio	1/1 Line input and output, 2 Way Audio
Remote configuration	web browser
Illumination range	approx. 45m
Weight	680g
Manufacturer order number	235341

Optional Accessory

SKU	Name	Description
233754	AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	AK-21	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
235339	AK-24	Dual camera connection box for Bullet or Fix Dome IN-Series cameras
218218	eneo Site Manager	Management Software for eneo IP products
236198	IPC Installation Tool	Supports adjustments for cameras with AI features for IN-series
235257	PM-21	Pole mounting adapter for camera connection box AK-20 and AK-21
235340	WB-24	Wall bracket for Dual camera connection box AK-24

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update

INB-52M2812M0A

Your contact person

SLD Security & Communications Ltd.
101 Eden Grove Road
KT14 7PX Byfleet Surrey
GB
Tel: +44.7973112104
E-Mail: enquiries@sld.uk
Web: www.sld.uk



SLD Security & Communications
Secure by Design