



IND-68M2713M0A

SKU: 235254



Network Dome Fix, 3840x2160, Day/Night, WDR, AI 2,7-13,5mm, IR, 12VDC, IP67

Main Features

- 1/2.8" Sony STARVIS CMOS sensor,8 MP/30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR Noise Reduction
- Motorized varifocal lens 2.7-13.5mm
- Smart Codec H.265/H.264, multi-streaming
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Supports ONVIF Profile S and Profile T
- Multilingual menu navigation (OSD)
- Local storage via Micro SD card
- Supports audio and external alarm input and output
- Power supply 12VDC or PoE IEEE 802.3af
- IR LED illumination, IP67 and vandal proof IK10

Specifications

Dimensions (HxWxD)	148.0x109.0mm
Series	eneo IN-Series
Camera Type	Face recognition, License plate recognition, People Count, Retail Intelligence
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	3840x2160

IND-68M2713M0A

Continuation of the specifications

Image Transmission Rate	30 fps
Day&Night Switch	ICR
Sensitivity	0,009 Lux
Sensitivity 2	at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	DOL-WDR 120dB, WDR 120dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
Horizontal Angle of View	111 - 33°
Vertical Angle of View	57 - 18°
Illumination	infrared
Housing	outdoor
Color (housing)	Pantone P 179-1, RAL9003
Color (bubble)	clear
Housing material	aluminium
Heater	no
Blower	no
Rotation range	350°
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	audio detection, Crowd detection, Face detection, face recognition, Heatmapping, intrusion, License plate detection, license plate recognition, Line detection, Object classification (person / vehicle), Object left,removed, Queue management, trip wire detection with counting and direction detection
Mounting_4	ceiling mount, wall mount
Supply voltage	12VDC, PoE
Power consumption	8W
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-35°C ~ +55°C, @ Humidity 90% or less (non-condensing)

IND-68M2713M0A

Continuation of the specifications

ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Certifications	IK10
Protection rating	IP67
Camera built	Dome
Audio	1/1 Line input and output, 2 Way Audio
Remote configuration	web browser
Illumination range	approx. 30m
Weight	950g
Manufacturer order number	235254

Optional Accessory

SKU	Name	Description
235339	AK-24	Dual camera connection box for Bullet or Fix Dome IN-Series cameras
235525	AK-25	Camera junction box for ceiling pipe DOME-CH6 and wall bracket DOME-WB6
235526	AK-26	Camera junction box for wall- and ceiling mount Fix dome cameras IN-Serie
218218	eneo Site Manager	Management Software for eneo IP products
236198	IPC Installation Tool	Supports adjustments for cameras with AI features for IN-series
235340	WB-24	Wall bracket for Dual camera connection box AK-24

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update

IND-68M2713M0A

Your contact person

SLD Security & Communications Ltd.
101 Eden Grove Road
KT14 7PX Byfleet Surrey
GB
Tel: +44.7973112104
E-Mail: enquiries@sld.uk
Web: www.sld.uk



SLD Security & Communications
Secure by Design