



INP-58M2812M0A

SKU: 234752



Netzwerk Dome, PTZ, 4x 3840x2160, Tag/Nacht, WDR, AI, Alarm, Audio, 12V, PoE, IP66

Main Features

-
- 1/2.7" CMOS sensor, maximum resolution 8 MP/30fps
-
- AI analysis functions including object classification
-
- D-WDR, 3D-DNR noise reduction
-
- Motorized varifocal lens 2.8-12mm
-
- Smart Codec H.265/H.264, multi-streaming
-
- Browser independent (IE, Edge, Safari, Firefox, Chrome)
-

-
- Supports ONVIF Profile S and Profile T
-
- Local storage via Micro SD card
-
- Supports audio and external alarm input and output
-
- Power supply 12VDC or PoE IEEE 802.3af
-
- IR LED lighting, IP66, deterrent (light & siren)
-
- Wall and ceiling mounting included
-

Specifications

Dimensions (HxWxD)	166,75x238mm
Series	eneo IN-Series
Camera Type	Face recognition, License plate recognition, People Count, Retail Intelligence
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/2.7"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	3640x2160

INP-58M2812M0A

Continuation of the specifications

Image Transmission Rate	25 fps
Day&Night Switch	ICR
Sensitivity	0,009 Lux
Sensitivity 2	at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	2,8 - 12 mm
Iris Control	DC
Digital Zoom	yes
Horizontal Angle of View	113 - 31,4°
Vertical Angle of View	58,4 - 17,6°
Illumination	infrared
Housing	outdoor
Color (housing)	black, Pantone P 179-1, RAL9003
Hosuing material	plastic
Heater	no
Blower	no
Rotation range	355°
Speed (manual)	0.6° to 45°/s°/Sek.
Speed (preset)	0.6° to 45°/s°/Sek.
Alarm inputs	no
Alarm outputs	no
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	audio detection, Crowd detection, Face detection, face recognition, Heatmapping, intrusion, license plate recognition, Line detection, Object classification (person / vehicle), Object left,removed, Queue management, trip wire detection with counting and direction detection
Mounting_4	ceiling mount, wall mount
Supply voltage	12VDC, PoE
Power consumption	13W
Vandal proof	no
Operating temperature	-30°C ~ +60°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T

INP-58M2812M0A

Continuation of the specifications

Protection rating	IP66
Camera built	PTZ
Audio	2 Way Audio, built-in loudspeaker, built-in microphone
Remote configuration	web browser
Illumination range	approx. 30m
Weight	920g
Manufacturer order number	234752

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
236198	IPC Installation Tool	Supports adjustments for cameras with AI features for IN-series

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update

Your contact person

SLD Security & Communications Ltd.
 101 Eden Grove Road
 KT14 7PX Byfleet Surrey
 GB
 Tel: +44.7973112104
 E-Mail: enquiries@sld.uk
 Web: www.sld.uk



SLD Security & Communications

Secure by Design