

Video Security



VK-1317S/W1

1/3" HiRes B&W Camera with 3.8mm lens
VHP-1 Housing, Wallbracket WD-21, 600TVL

Art-Nr. 96048



Features

B&W Board Camera VK-1317 in Weatherproof Housing

1/3" CCD Sensor Chip

Resolution of 600 Horizontal Lines

Electronic Shutter Control (ESC)

High Sensitivity

Integrated Lens: F2.0/3.8 mm

Supply Voltage: 12 VDC

Compact Version

Index of Protection: IP67

Protected Pan and Tilt Fixing Mechanism

Wall Bracket Included

Specifications

| | |
|--|---|
| Imager | 1/3" Sony Super HAD Interline Transfer CCD |
| System | CCIR |
| Synchronization | Internal |
| Sensitivity at 50% video signal | 2.1Lux at F2.0 / 0.76Lux at F1.2 (VT measurement result) |
| Horizontal resolution | 600 TV lines |
| Active picture elements | Approx. 440,000 (H) 752 x (V) 582 |
| Electronic shutter (ESC) | 1/50 to 1/100,000 sec. |
| Video output | 1 Vp-p, VBS, 75 ohms |
| Gamma correction | 0.45 |
| Integrated lens | F2.0/3.8mm w./o. iris |
| Aperture Correction (APC) | Yes (horizontal) |
| Horizontal angle of view | 65° |
| Heater/sunshield | No |
| Cable entry | Wiring for video and voltage supply made, accessible from outside |
| Supply voltage | 12 VDC +/-10 % |
| Power consumption | Approx. 1.4watts |
| Housing | Aluminium with glass screen |

VK-1317S/W1

(Specifications continued)

| | |
|------------------------------------|--|
| Colour | Anodized aluminium (CO) |
| Protection rating | IP 67 |
| Temperature range | -30°C to +40°C |
| Dimensions (HxWxD) | See drawing |
| Weight (w./o. wall bracket) | 280 g |
| Parts supplied | Wall bracket WD-21/MK, 3mm Allen wrench key, Bag of screws |

Accessories

| | |
|----------------------------|--|
| 40061 / H0820M | F2.0/8mm Board Camera Lens, 1/3" |
| 40072 / H0620M | F2.0/6mm Board Camera Lens, 1/3" |
| 40065 / H1225 | F2.5/12mm Board camera lens, 1/3" |
| 70448 / VT-PS12DC-6 | Plug-in Power Supply 230VAC/12VDC (1.0A) |
| 77772 / VT-PS12DCDT | PSU 12VDC/0,5A, Desktop version |

