

Plug & Play Camera Packs

1/4" Candid Junior B/W Camera Package,
weatherproof, 12VDC, 380TVL

EDP-No.: 96006

VKC-144/W1

- Colour Brd. Camera VKC-144 in Weatherproof Housing
- 1/4" CCD Sensor Chip
- Resolution of 380 Horizontal Lines
- Electronic Shutter Control (ESC)
- High Sensitivity
- Integrated Lens: F2.0/3.6 mm
- Supply Voltage: 12 VDC
- Insulated Camera Mounting
- Compact Version
- Index of Protection: IP67
- Wall Bracket Included



Specifications:

Imager	1/4" Sony Super HAD Interline Transfer CCD
System	CCIR/PAL
Synchronization	Internal
Sensitivity at 50% video signal	1.4 Lux at F2.0 (VT measurement result)
Horizontal resolution	380 TV lines
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Electronic shutter (ESC)	1/50 to 1/100,000 sec.
Video output	1 Vp-p, CVBS, 75 ohms
Gamma correction	Approx. 0.45
Integrated lens	F2.0/3.6 mm w./o. iris
Aperture Correction	Yes (horizontal)
Heater/sunshield	No
Cable entry	Wiring for video and voltage supply made, accessible from outside
Supply voltage	12 VDC +/-10 %
Power consumption	Approx. 1.5 watts
Housing	Aluminium with glass screen
Colour	Anodized aluminium (CO)
Protection rating	IP 66/67

VKC-144/W1

Temperature range	-30°C to +40°C
Dimensions (HxWxD)	See drawing
Weight (w./o. wall bracket)	280 g
Parts supplied	Wall bracket WD-21/MK, 3mm Allen wrench key, Bag of screws

Accessories	
EDP No. / Type	Description
40061 H0820M	F2,0/8mm Board Camera Lens, 1/3", M12X0,5
70442 VT-PS12DC-3	Power Supply 230VAC/12VDC(500mA), stabilized
77779 VT-PS12DC-UK	Plugable PSU 12VDC-500mA, stabilized with UK mains plug, open DC lead
40065 H1225	F2.5/12mm Board camera lens 1/3", M12x0.5mm
40072 H0620M	F2.0/6mm Board camera lens 1/3", M12x0.5

