

VTL-WWA-BL

Home | Security | Housings | for Boxed Cameras

VTL-WWA-BL

Weatherproof Housing (300mm) Heater, Blower,

Wallbracket, RAL9002, PSU 230V

Art-Nr. 79717



SLD Security &
Communications

Main Features

Weather protection for cameras
Integrated wall bracket
Fold-down housing body
Insulated camera mounting
Housing body length: 300mm

Cable entry through the wall bracket
230V window heater included
Blower included
Protection rating: IP66
Housing colour: RAL9002

Specifications

Series	eneo VTL
Maximum installation length	300
Clear Shield	no
Window heater	yes, 100~240V/40W (PTC)
Blower	yes
Wiper	no
Supply voltage	100~240VAC
Sunshield	yes
Hidden cable management	yes
Cable entry	Through the wall bracket
Integrated wall mount	yes
Protection rating	IP66
Housing	outdoor
Housing material	aluminium

VTL-WWA-BL

(Continuation Specifications)

Colour (housing)	RAL9002
Temperature range	-20°C ~+50°C
Dimensions (HxWxD)	see drawing
Weight	4.0kg
Certificates	CE

Optional accessories

70457	AK-3	Camera Connection box, 230VAC Input, 24VAC-3.2A, 12VDC-1A Outputs
79593	PM-6D	Pole Mount Adapter for 2 Wall Mounts, (50-140mm Pole), RAL9002
79592	PM-6S	Pole Mount Adapter for 1 Wall Mount, (50-140mm Pole), RAL9002
77345	VTL-BL-230V	Blower, with Thermostat 230V, for VTL-WWA housing
79604	SU-6	Camera Height Adjustment Kit for VHK and EHL Housings (3 Diff. Slides and Screws)
79662	NE-130/12V	Power Supply Unit 230V/12VDC-1.25A for Housings VTL-WWA
79613	CMA-2	Corner Mount Adapter for Wall Brackets WD-5, WD-7, VTL-WW, VHK-WW, RAL9002

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

